## NSN 6110-01-312-8557

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-312-8557

| Speed Adjustments:  |
|---|
| Single speed  |
| Hazardous Locations/environmental Protection:                   |
| Spraytight  |
| Overall Length:   |
| 20.000 inches   |
| Overall Width:  |
| 13.000 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Performance Type:   |
| Manual and automatic  |
| Size Designator:  |
| 4   |
| Duty Cycle:   |
| Continuous  |
| Load Protection Type:   |
| Overload and undervoltage                                       |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Open  |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std   |
| Switch Functional Positions:                                    |
| Start and standby and reset and off                             |
| Control Type:   |
| Local or remote   |
| Features Provided:  |
| Circuit protection fuse   |
| Phase:  |
| Three   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 6110-01-312-8557

Motor Starter - Page 2 of 2



Fiig:

A541c0