NSN 6110-01-313-7147

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-313-7147

| Speed Adjustments: |
|---|
| Single speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 20.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Electrical control equipment |
| Fuse Accommodation Quantity: |
| 4 |
| Size Designator: |
| 3 |
| Duty Cycle: |
| Continuous |
| Horsepower Rating: |
| 50.000 |
| Fuse Current Rating In Amps: |
| 3.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Start and stop and test and emergency run |
| Control Type: |
| Local or remote |
| Features Provided: |
| Circuit protection fuse |
| Phase: |
| Three |
| Shelf Life: |

N/a

NSN 6110-01-313-7147

Motor Starter - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A541c0