NSN 6110-01-315-2994

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-315-2994

Speed Adjustments:
Single speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
48.780 inches
Overall Height:
44.800 inches
Overall Width:
34.120 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Electrical control equipment
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
4 and 4
Size Designator:
Size Designator:
_
3
3 Duty Cycle:
3 Duty Cycle: Continuous
3 Duty Cycle: Continuous Mounting Configuration:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 6.0 and 10.0
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 6.0 and 10.0 Load Protection Type:
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 6.0 and 10.0 Load Protection Type: Overload and undervoltage
Duty Cycle: Continuous Mounting Configuration: Eight 21/32 diameter holes for 5/8 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 50.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 6.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp:

NSN 6110-01-315-2994

Motor Controller - Page 2 of 2

Fiig: A541b0



National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: -Demilitarization: No