NSN 6110-01-316-0741

Hazardous Locations/environmental Protection:

Motor Controller - Page 1 of 2

Speed Adjustments:

Two speed

Dripproof

Overall Length: 36.000 inches Overall Height: 36.000 inches



View Online at https://aerobasegroup.com/nsn/6110-01-316-0741

Overall Width:
24.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Vent fan
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
2
Size Designator:
2
Duty Cycle:
Continuous
Mounting Configuration:
Mounting Configuration: Eight 15/32 holes for 7/16 mtg bolts
Eight 15/32 holes for 7/16 mtg bolts
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage Ambient Temp:
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius
Eight 15/32 holes for 7/16 mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 15.000 and 4.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius Inclosure Feature:

NSN 6110-01-316-0741

Motor Controller - Page 2 of 2

Fiig: A541b0



National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 45.0 and 18.0 **Switch Functional Positions:** Slow and fast start and slow start and emergency run and fast **Control Type:** Local or remote **Features Provided:** Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a **Unit Of Measure: Demilitarization:** No