NSN 6110-01-317-3778

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-317-3778

Speed Adjustments:
Single speed
Overall Length:
18.000 inches
Overall Height:
8.375 inches
Overall Width:
18.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Pressurization fan
Performance Type:
Manual and automatic
Fuse Accommodation Quantity:
1 and 2
Size Designator:
2
Duty Cycle:
Continuous
Operating Voltage Characteristic:
Operating Voltage Characteristic:
Full
Full Horsepower Rating:
Full Horsepower Rating: 25.000
Full Horsepower Rating: 25.000 Actuator Voltage:
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps:
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type:
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp:
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius Inclosure Feature:
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius Inclosure Feature: Dripproof
Full Horsepower Rating: 25.000 Actuator Voltage: 115.0 ac Fuse Current Rating In Amps: 3.0 and 10.0 Load Protection Type: Overload and undervoltage Ambient Temp: 50.0 degrees celsius Inclosure Feature: Dripproof National Electrical Manufacturers Association Standards Design:

NSN 6110-01-317-3778

Motor Starter - Page 2 of 2



Switch Functional Positions: Start and stop and emergency run Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A541c0