NSN 6110-01-317-3779

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-317-3779

| Speed Adjustments: |
|---|
| Single speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 44.200 inches |
| Overall Height: |
| 50.600 inches |
| Overall Width: |
| 34.200 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Mooring-anchor windlass |
| Performance Type: |
| Manual or automatic |
| Fuse Accommodation Quantity: |
| 2 |
| Size Designator: |
| 6 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Nine 21/32 diameter holes for 5/8 mtg bolts |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 250.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 30.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |

NSN 6110-01-317-3779

Motor Starter - Page 2 of 2

Fiig: A541c0



National Electrical Manufacturers Association Standards Design: Designed per nema std **Switch Functional Positions:** Emergency run and start and stop **Control Type:** Local or remote **Features Provided:** Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a **Unit Of Measure:** Demilitarization: No