NSN 6110-01-318-6533

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-318-6533

Speed Adjustments:
Single speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
20.120 inches
Overall Height:
22.800 inches
Overall Width:
14.120 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Electrical control equipment
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
2
Size Designator:
Size Designator:
_
0
0 Duty Cycle:
0 Duty Cycle: Continuous
O Duty Cycle: Continuous Mounting Configuration:
O Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type:
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage
Duty Cycle: Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 5.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Overload and undervoltage Ambient Temp:

NSN 6110-01-318-6533

Motor Starter - Page 2 of 2

Fiig: A541c0



National Electrical Manufacturers Association Standards Design: Designed per nema std **Switch Functional Positions:** Manual and automatic **Control Type:** Local or remote **Features Provided:** Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a **Unit Of Measure:** Demilitarization: No