## NSN 6110-01-322-8373

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-322-8373

Speed Adjustments:
Two speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
36.120 inches
Overall Height:
36.560 inches
Overall Width:
26.100 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Sliding block transfer systems
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
2
Size Designator:
4
Duty Cycle:
Continuous and variable
Mounting Configuration:
Eight 21/32 diameter holes for 5/8 mtg bolts
Operating Voltage Characteristic:
Full
Horsepower Rating:
Horsepower Rating: 75.000 and 37.500
-
75.000 and 37.500
75.000 and 37.500 Actuator Voltage:
75.000 and 37.500  Actuator Voltage: 440.0 ac
75.000 and 37.500  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps:
75.000 and 37.500  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0
75.000 and 37.500  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0  Load Protection Type:
75.000 and 37.500  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0  Load Protection Type:  Overload and undervoltage
75.000 and 37.500  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0  Load Protection Type:  Overload and undervoltage  Ambient Temp:

## NSN 6110-01-322-8373

Motor Controller - Page 2 of 2

Fiig: A541b0



## National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: --Demilitarization: No