NSN 6110-01-323-1967

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-323-1967

| Speed Adjustments: |
|--|
| Single speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 18.120 inches |
| Overall Height: |
| 22.800 inches |
| Overall Width: |
| 14.120 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Electrical control equipment |
| Performance Type: |
| Automatic or manual |
| Fuse Accommodation Quantity: |
| 1 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 diameter holes for 1/2 in mtg bolts |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload or undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |

Dripproof

NSN 6110-01-323-1967

Motor Starter - Page 2 of 2

Fiig: A541c0



| National Electrical Manufacturers Association Standards Design: |
|---|
| Designed per nema std |
| Amp Size Rating: |
| 20.8 |
| Control Type: |
| Local or remote |
| Features Provided: |
| Circuit protection fuse |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |