NSN 6110-01-327-8416

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-327-8416

Single speed
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
18.120 inches
Overall Height:
20.800 inches
Overall Width:
12.100 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Electrical control equipment
Performance Type:
Automatic and manual
Fuse Accommodation Quantity:
4
Size Designator:
1
Duty Cycle:
Continuous
Continuous
Continuous Mounting Configuration:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type:
Continuous Mounting Configuration: Four 17/32 diameter holes for 1/2 in mtg bolts Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 Load Protection Type: Undervoltage and overload

Waterproof

NSN 6110-01-327-8416

Motor Starter - Page 2 of 2

Fiig: A541c0



National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local or remote Features Provided: Circuit protection fuse Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: --Demilitarization: No