NSN 6110-01-332-7041

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-332-7041

| Speed Adjustments: |
|---|
| Single speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 40.360 inches |
| Overall Height: |
| 42.800 inches |
| Overall Width: |
| 30.100 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Hauling winch |
| Fuse Accommodation Quantity: |
| 2 and 6 |
| Size Designator: |
| 5 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Eight 21/32 diameter holes for 5/8 in mtg bolts |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 200.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 and 20.0 |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Control Type: |
| Local |

NSN 6110-01-332-7041

Motor Starter - Page 2 of 2



| Features | Provided: |
|----------|-----------|
| reatures | riovided. |

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A541c0