NSN 6110-01-334-0212

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-334-0212

| Hazardous Locations/environmental Protection: | | | | | |
|---|--|--|--|--|--|
| Dripproof | | | | | |
| Overall Length: | | | | | |
| 24.000 inches | | | | | |
| Overall Height: | | | | | |
| 8.000 inches | | | | | |
| Overall Width: | | | | | |
| 16.000 inches | | | | | |
| Ac Voltage Rating: | | | | | |
| 440.0 volts | | | | | |
| Frequency Rating: | | | | | |
| 60.0 hertz | | | | | |
| Actuation Method: | | | | | |
| Magnetic | | | | | |
| Fuse Accommodation Quantity: | | | | | |
| 4 | | | | | |
| Duty Cycle: | | | | | |
| Continuous | | | | | |
| Mounting Configuration: | | | | | |
| Four 15/32 diameter mtg holes on 14-1/2 in by 22 in ctr | | | | | |
| Operating Voltage Characteristic: | | | | | |
| Full | | | | | |
| Horsepower Rating: | | | | | |
| 10.000 | | | | | |
| Actuator Voltage: | | | | | |
| 110.0 ac | | | | | |
| Fuse Current Rating In Amps: | | | | | |
| 10.0 and 30.0 | | | | | |
| Ambient Temp: | | | | | |
| 50.0 degrees celsius | | | | | |
| Inclosure Feature: | | | | | |
| Dripproof | | | | | |
| National Electrical Manufacturers Association Standards Design: | | | | | |
| Not designed per nema std | | | | | |
| Amp Size Rating: | | | | | |
| 30.0 | | | | | |
| Control Type: | | | | | |
| Local | | | | | |
| Features Provided: | | | | | |
| Circuit protection fuse | | | | | |
| Phase: | | | | | |

Three

NSN 6110-01-334-0212

Motor Starter - Page 2 of 2



| | F | rea | uency | In I | Hertz: |
|--|---|-----|-------|------|--------|
|--|---|-----|-------|------|--------|

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0