NSN 6110-01-334-3956

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-334-3956

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Length: |
| 16.000 inches |
| Overall Height: |
| 22.000 inches |
| Overall Width: |
| 10.000 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 2 |
| Size Designator: |
| 2 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 25.000 |
| Actuator Voltage: |
| 115.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Ambient Temp: |
| 50.0 degrees celsius |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Amp Size Rating: |
| 45.0 |
| Control Type: |
| Local |
| Features Provided: |
| Circuit protection fuse |
| Phase: |
| Three |

NSN 6110-01-334-3956

Motor Starter - Page 2 of 2



| Frequency In | Hertz: |
|--------------|--------|
|--------------|--------|

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0