## NSN 6110-01-334-3959

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-334-3959

| Speed Adjustments:  |
|---|
| Single speed  |
| Hazardous Locations/environmental Protection:                   |
| Dripproof   |
| Overall Length:   |
| 22.000 inches   |
| Overall Height:   |
| 22.000 inches   |
| Overall Width:  |
| 14.000 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| End Application:  |
| Electrical control equipment                                    |
| Fuse Accommodation Quantity:                                    |
| 2   |
| Size Designator:  |
| 0   |
| Duty Cycle:   |
| Continuous  |
| Mounting Configuration:   |
| Four 15/32 in holes for 7/16 in mtg bolts                       |
| Operating Voltage Characteristic:                               |
| Full  |
| Horsepower Rating:  |
| 5.000   |
| Actuator Voltage:   |
| 115.0 ac  |
| Fuse Current Rating In Amps:                                    |
| 6.0   |
| Load Protection Type:   |
| Overload and undervoltage                                       |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Dripproof   |
| National Electrical Manufacturers Association Standards Design: |
| Design and resource and   |

Designed per nema std

## NSN 6110-01-334-3959

Motor Starter - Page 2 of 2



| Amp Size Rating:        |
|-------------------------|
| 18.0                    |
| Control Type:           |
| Local or remote         |
| Features Provided:      |
| Circuit protection fuse |
| Phase:                  |
| Three                   |
| Frequency In Hertz:     |
| 60.0                    |
| Shelf Life:             |
| N/a                     |
| Unit Of Measure:        |
|                         |
| Demilitarization:       |

No Fiig: A541c0