

View Online at <https://aerobasegroup.com/nsn/6110-01-356-2578>

Hazardous Locations/environmental Protection:

Watertight-nema type 4

Overall Depth:

12.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches

Overall Height:

16.000 inches

Overall Width:

6.000 inches

Material Thickness:

0.080 inches

Mounting Slot Width:

0.625 inches

Mounting Slot Length:

0.625 inches

Furnished Items And Quantity:

1 cap and chain and 1 gasket and 12 terminal board

Unthreaded Mounting Hole Diameter:

0.438 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

17.250 inches

Standard Mounting Pattern Designator:

4 point-rectangular

Cable Entrance Diameter:

0.588 inches and 0.599 inches and 0.125 inches and 0.250 inches

End Application:

9x35 lr buoy

Unpackaged Unit Weight:

15.000 pounds

Mounting Method:

Bracket with hole and slot

Circuit Breaker Type And Quantity:

1 single pole

Circuit Breaker Current Rating In Amps:

10.0

Switch Type And Quantity:

1 toggle

Terminal Type And Quantity:

58 screw

Entrance Type And Quantity:

7 stuffing box

Special Features:

Includes wave activated generator controller

Functional Description:

Provides watertight housing protection for input and output connections, w.A.G. Controller and power distribution for the system

Material:

Steel

Style Designator:

Rectangular, surface mounting

Test Data Document:

0r6-6-397 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

0r6-6-397 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A17600