Phase: Three



| <b>NSN 6110-01-358-8101</b><br>Motor Starter - Page 1 of 2      |
|---|
| View Online at https://aerobasegroup.com/nsn/6110-01-358-8101   |
| Hazardous Locations/environmental Protection:                   |
| Dripproof   |
| Overall Length:   |
| 14.000 inches   |
| Overall Height:   |
| 16.000 inches   |
| Overall Width:  |
| 8.000 inches  |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Performance Type:   |
| Manual  |
| Fuse Accommodation Quantity:                                    |
| 2   |
| Size Designator:  |
| 0   |
| Duty Cycle:   |
| Continuous  |
| Operating Voltage Characteristic:                               |
| Full  |
| Horsepower Rating:  |
| 5.000   |
| Actuator Voltage:   |
| 220.0 ac  |
| Fuse Current Rating In Amps:                                    |
| 3.0   |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std   |
| Amp Size Rating:  |
| 18.0  |
| Control Type:   |
| Local   |
| Features Provided:  |
| Circuit protection fuse   |
|   |

## NSN 6110-01-358-8101

Motor Starter - Page 2 of 2

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A541c0

