Motor Controller - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-01-409-2017

Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Actuator Voltage: 440.0 ac 440.0 ac	Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: Na Unit Of Measure: Demilitarization:	Speed Adjustme	ts:	
440.0 vols Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shef Life: N/a Unit Of Measure: Demilitarization: No	440.0 vorts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Fuil Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	0 to full speed		
Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Shel Life: N/a Unit Of Measure: Demilitarization: No	Frequency Rating: 60.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Fuil Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Ac Voltage Ratin	:	
80.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: Na Unit Of Measure: Demilitarization: No	80.0 hertz Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.00 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Sheff Life: N/a Unit Of Measure: Demilitarization:	440.0 volts		
Actuation Method: Magnetic Performance Type: Automatic Size Designator: Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Sheff Life: N/a Unit of Measure: Demilitarization: No	Actuation Method: Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: Na Unit Of Measure: Demilitarization:	Frequency Rating	:	
Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Sheff Life: N/a Unit Of Measure: Demilitarization: No	Magnetic Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Sheff Life: N/a Unit Of Measure: Demilitarization:	60.0 hertz		
Performance Type: Automatic Size Designator: I Size Designator: I Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Performance Type: Automatic Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit of Measure: 	Actuation Metho	:	
Automatic Size Designator: Size Designat	Automatic Size Designator: I Size Designator: I U Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: I0.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit of Measure: Demilitarization:	Magnetic		
Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Size Designator: 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Performance Typ	»:	
1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Automatic		
Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Denilitarization:	Size Designator:		
Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Denilitarization:	1		
Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: Na Unit Of Measure: Demilitarization: No	Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Duty Cycle:		
Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Continuous		
Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: 	Operating Voltag	Characteristic:	
10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	10.000 Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Denilitarization:	Full		
Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Actuator Voltage: 440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: 	Horsepower Rati	g:	
440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	440.0 ac Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: 	10.000		
Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: 	Actuator Voltage		
Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Overload Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	440.0 ac		
Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Ambient Temp: 50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: 	Load Protection	уре:	
50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	50.0 degrees celsius National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Overload		
National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Designed per nema	Ambient Temp:		
Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Designed per nema std Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	50.0 degrees cels	IS	
Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Control Type: Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	National Electric	I Manufacturers Association Standards Design:	
Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Local Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Designed per nem	a std	
Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Phase: Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Control Type:		
Three Shelf Life: N/a Unit Of Measure: Demilitarization: No	Three Shelf Life: N/a Unit Of Measure: Demilitarization:	Local		
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Shelf Life: N/a Unit Of Measure: Demilitarization:	Phase:		
N/a Unit Of Measure: Demilitarization: No	N/a Unit Of Measure: Demilitarization:	Three		
Unit Of Measure: Demilitarization: No	Unit Of Measure: Demilitarization:	Shelf Life:		
 Demilitarization: No	 Demilitarization:	N/a		
Demilitarization: No	Demilitarization:	Unit Of Measure:		
Νο				
	No	Demilitarization:		
Fiig:		No		
	Fiig:	Fiig:		