## NSN 6110-01-482-1815

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-482-1815

29.120 inches Overall Width: 17.380 inches Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided: Circuit protection fuse
17.380 inches Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Ac Voltage Rating: 440.0 volts Frequency Rating: 60.0 hertz Actuation Method: Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
440.0 volts  Frequency Rating: 60.0 hertz  Actuation Method: Magnetic  Fuse Accommodation Quantity: 8  Size Designator: 1  Duty Cycle: Continuous Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0 and 5.0  Load Protection Type: Overload  Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Frequency Rating: 60.0 hertz  Actuation Method: Magnetic  Fuse Accommodation Quantity: 8  Size Designator: 1  Duty Cycle: Continuous  Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0 and 5.0  Load Protection Type: Overload  Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight  National Electrical Manufacturers Association Standards Design: Designed per nema std  Features Provided:
Actuation Method: Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Actuation Method: Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Magnetic Fuse Accommodation Quantity: 8 Size Designator: 1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Fuse Accommodation Quantity:  8 Size Designator:  1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Size Designator:  1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Size Designator:  1 Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Duty Cycle: Continuous Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Continuous  Operating Voltage Characteristic: Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0 and 5.0  Load Protection Type: Overload  Ambient Temp: 50.0 degrees celsius  Inclosure Feature: Watertight  National Electrical Manufacturers Association Standards Design: Designed per nema std  Features Provided:
Operating Voltage Characteristic: Full Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Full  Horsepower Rating: 10.000  Actuator Voltage: 440.0 ac  Fuse Current Rating In Amps: 10.0 and 5.0  Load Protection Type: Overload  Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight  National Electrical Manufacturers Association Standards Design: Designed per nema std  Features Provided:
Horsepower Rating: 10.000 Actuator Voltage: 440.0 ac Fuse Current Rating In Amps: 10.0 and 5.0 Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Actuator Voltage:  440.0 ac  Fuse Current Rating In Amps:  10.0 and 5.0  Load Protection Type:  Overload  Ambient Temp:  50.0 degrees celsius  Inclosure Feature:  Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
Actuator Voltage:  440.0 ac  Fuse Current Rating In Amps:  10.0 and 5.0  Load Protection Type:  Overload  Ambient Temp:  50.0 degrees celsius  Inclosure Feature:  Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
440.0 ac  Fuse Current Rating In Amps:  10.0 and 5.0  Load Protection Type:  Overload  Ambient Temp:  50.0 degrees celsius  Inclosure Feature:  Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
Fuse Current Rating In Amps:  10.0 and 5.0  Load Protection Type:  Overload  Ambient Temp:  50.0 degrees celsius  Inclosure Feature:  Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
10.0 and 5.0  Load Protection Type:  Overload  Ambient Temp:  50.0 degrees celsius  Inclosure Feature:  Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
Load Protection Type: Overload Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Overload  Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Ambient Temp: 50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
50.0 degrees celsius Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Inclosure Feature: Watertight National Electrical Manufacturers Association Standards Design: Designed per nema std Features Provided:
Watertight  National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
National Electrical Manufacturers Association Standards Design:  Designed per nema std  Features Provided:
Designed per nema std  Features Provided:
Features Provided:
Circuit protection fuse
Product Name:
Controller a.C. Magnetic size 1
Phase:
Three
Shelf Life:
Shelf Life: N/a

--

## NSN 6110-01-482-1815

Motor Starter - Page 2 of 2



Demilitarization:

No

Fiig:

A541c0