

View Online at <https://aerobasegroup.com/nsn/6110-01-495-6316>

Furnished Items And Quantity:

2 terminal board and 1 cover

Standard Mounting Pattern Designator:

4 point-rectangular

End Application:

7010-01-391-0168

Mounting Method:

Bracket with hole

Circuit Breaker Type And Quantity:

6 single pole

Circuit Breaker Current Rating In Amps:

5.0 and 15.0

Switch Type And Quantity:

1 toggle

Circuit Breaker Manufacturer Code:

81349

Err Default:

Err default

Err Default:

Err default

Product Name:

Circuit breaker panel assembly-bay 3

Special Features:

Workmanship shall be in accordance with mil-hdbk-454; remove and discard circuit breaker on-off plate; torque threaded fasteners as follows: .112-40-3to5 in/lb (connectors, cover mtg).138-32-5 to 8 in/lbs(circuit breaker terminals).164-32-8 to11 in/lbs(tb1, tb2 mounting/terminals); .190-32-11 to 15 in/lbs(e1, enclosure mtg); mark find no.40 wire markers, per wiring table, sheet 2 and locate at all applicable wire terminations.Mark with .19 high characters per mil-std-130 using black ink per a-a-208; rubber stamp or stencil the following markings in accordance with mil-std-130 using black ink a-a-208 at location shown.Character size shall be .13 +/- .02 high.(01365assy97008a3100)

Style Designator:

Square, flush mounting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A17600