

| Motor Starter - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/6110-01-503-3557 |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Height: |
| 18.120 inches |
| Overall Width: |
| 12.120 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Manual |
| End Application: |
| Controller, ac type qa0 |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 2 |
| Duty Cycle: |
| Continuous |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 5.000 |
| Fuse Current Rating In Amps: |
| 10.0 |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Not designed per nema std |
| Control Type: |
| Local |
| Features Provided: |
| Circuit protection fuse |
| Product Name: |
| (inaw)controller motor (drawing)motor controller modas svc nump assembly |

(inavy)controller, motor (drawing)motor controller mogas svc pump assembly(215-345-010)

Phase:

Three

Shelf Life:

N/a

NSN 6110-01-503-3557

Motor Starter - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A541c0

