

| Motor Controller - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/6110-01-526-9773 |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 18.120 inches |
| Overall Height: |
| 12.120 inches |
| Overall Width: |
| 9.140 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Motor controller fca-35 fan motor assembly |
| Fuse Accommodation Quantity: |
| 8 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Wall mount; 4 bolts 0.500 inches dia, grade (min) ; torque to 90lb-ft |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 30.0 and 10.0 |
| Load Protection Type: |
| Overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Reset and start and stop

NSN 6110-01-526-9773

Motor Controller - Page 2 of 2



Control Type:

Local

Features Provided:

Accessory location internal and circuit protection fuse

Product Name:

Motor controller, type n850

Phase:

Three

Special Features:

Enclosure & components are shockproof, grade a, class 1 of mil-s-901; cps reference: type 1a1

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0