# NSN 6110-01-527-3386

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-527-3386

## Hazardous Locations/environmental Protection:

Dripproof and watertight and submersible and hazardous location, class i, group d, nema type 7 and moisture resistant

## **Overall Length:**

17.300 inches

## **Overall Height:**

9.380 inches

## Overall Width:

8.060 inches

## Ac Voltage Rating:

440.0 volts

## Frequency Rating:

60.0 hertz

## Actuation Method:

Magnetic

#### **End Application:**

Starter, motor

## Fuse Accommodation Quantity:

1

#### Size Designator:

2

### Duty Cycle:

Continuous

## Mounting Configuration:

4 each 17/32 inch diameter holes for 1/2 inch mounting bolts through enclosure wall

## **Operating Voltage Characteristic:**

Full

#### Horsepower Rating:

25.000

#### Actuator Voltage:

440.0 ac

## **Fuse Current Rating In Amps:**

10.0

## Load Protection Type:

Undervoltage and overload

## Ambient Temp:

50.0 degrees celsius

## Inclosure Feature:

Dripproof and splash proof and submersible

## National Electrical Manufacturers Association Standards Design:

Designed per nema std

## Amp Size Rating:

45.0

# NSN 6110-01-527-3386

Motor Controller - Page 2 of 2



#### **Switch Functional Positions:**

Start and stop and reset and emergency run and emergency stop

### Control Type:

Local

## Features Provided:

Accessory location internal and circuit protection fuse

#### **Product Name:**

Controller, ac magnetic size 2

## Phase:

Three

### **Special Features:**

Enclosure & components are shockproof, grade a, class 1 of mil-s-901; contactor n894; across-the-line operation

### Frequency In Hertz:

60.0

#### Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

## Fiig:

A541b0