

View Online at <https://aerobasegroup.com/nsn/6110-01-528-1489>

Frequency Rating:

60.0 hertz

Switch Position Quantity:

2

End Application:

Auto bus transfer swit abt-1a2-100

Current Rating In Amps:

100.0

Inclosure Feature:

Dripproof

Switch Operation Method:

Manual

Switch Action Type:

Rotary

Manual Operation Facility:

Provided

Voltage In Volts:

120.0

Phase:

Three

Special Features:

Solenoid lock replaced by warning lite. 2 fuses with blown indicators protect l4 coil, ctrl panel & wiring if prevented from completing operation due to blockage/outside forces; 2 position cntrl disconnect switch replaces the 3 position switch. Insures proper sequencing oof abt when restored from manual to auto op; control contact assembly is incorporating non-adjustable cams, drive link bushings prevent overtight of lock nuts, & stronger drives linkages replace the previous assembly.

Relationship To Similar Equipment:

REPL-AC-EME-NT/U

Supplementary Features:

Chgs made to prevent nuisance transfers when both sources are energized simultaneously, also when a short outage of both sources, when both sources are inphase. New instruction plate provides operational info with new revisions and new laminated wiring card are provided.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-q