

View Online at <https://aerobasegroup.com/nsn/6110-01-528-1489>

**Frequency Rating:**

60.0 hertz

**Switch Position Quantity:**

2

**End Application:**

Auto bus transfer swit abt-1a2-100

**Current Rating In Amps:**

100.0

**Inclosure Feature:**

Dripproof

**Switch Operation Method:**

Manual

**Switch Action Type:**

Rotary

**Manual Operation Facility:**

Provided

**Voltage In Volts:**

120.0

**Phase:**

Three

**Special Features:**

Solenoid lock replaced by warning lite. 2 fuses with blown indicators protect I4 coil, ctrl panel & wiring if prevented from completing operation due to blockage/outside forces; 2 position cntrl disconnect switch replaces the 3 position switch. Insures proper sequencing oof abt when restored from manual to auto op; control contact assembly is incorporating non-adjustable cams, drive link bushings prevent overtight of lock nuts, & stronger drives linkages replace the previous assembly.

**Relationship To Similar Equipment:**

REPL-AC-EME-NT/U

**Supplementary Features:**

Chgs made to prevent nuisance transfers when both sources are energized simultaneously, also when a short outage of both sources, when both sources are inphase. New instruction plate provides operational info with new revisions and new laminated wiring card are provided.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T142-q