## NSN 6110-01-528-7878

Motor Controller - Page 1 of 2



| view Online at https://aerobasegroup.com/hsh/o110-01-526-7676  |
|--|
| Hazardous Locations/environmental Protection:  |
| Dripproof  |
| Overall Length:  |
| 18.120 inches  |
| Overall Width:   |
| 12.120 inches  |
| Ac Voltage Rating:   |
| 440.0 volts  |
| Frequency Rating:  |
| 60.0 hertz   |
| Actuation Method:  |
| Magnetic   |
| End Application:   |
| Motor controller tpes-74 fan motor assembly  |
| Fuse Accommodation Quantity:   |
| 2 and 2  |
| Duty Cycle:  |
| Continuous   |
| Operating Voltage Characteristic:  |
| Full   |
| Horsepower Rating:   |
| 10.000   |
| Actuator Voltage:  |
| 440.0 ac   |
| Fuse Current Rating In Amps:   |
| 10.0 and 5.0   |
| Ambient Temp:  |
| 50.0 degrees celsius   |
| Amp Size Rating:   |
| 30.0   |
| Control Type:  |
| Local  |
| Features Provided:   |
| Circuit protection fuse  |
| Product Name:  |
| Inavy: controller motor  |
| Phase:   |
| Three  |
| Special Features:  |
| Cps reference: type 5b1; controller weight: 52 lbs (est), repair parts (unboxed) rsvd; type: across the line; shockproofness: grade a, class |
| 1 of mil-s-901; no exceptions to military spec. Mil-c-2212h; (hull c6017a/b/c/d); contactor, magnetic, ac, size 1.                           |

60.0

Frequency In Hertz:

## NSN 6110-01-528-7878

Motor Controller - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A541b0