NSN 6110-01-535-7138

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-535-7138

| Hazardous Locations/environmental Protection: |
|---|
| Dripproof |
| Overall Length: |
| 14.100 inches |
| Overall Height: |
| 18.120 inches |
| Overall Width: |
| 10.500 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Motor terminals |
| Fuse Accommodation Quantity: |
| 3 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32dia holes forr 1/2dia mounting bolts |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Undervoltage and overload |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Slow and fast and stop and safe-run |

NSN 6110-01-535-7138

Motor Controller - Page 2 of 2



| Control Type: |
|---|
| Local or remote |
| Features Provided: |
| Accessory location external and circuit protection fuse |
| Product Name: |
| Controller a.C. Magnetic 2 speed 2 winding size 1 |
| Phase: |
| Three |
| Special Features: |
| Shockproof grade a class 1 of mil-s-901; 2 speed 2 windings |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541b0 |