

View Online at <https://aerobasegroup.com/nsn/6110-01-537-1111>

Hazardous Locations/environmental Protection:

Watertight and dripproof

Overall Length:

19.380 inches

Overall Height:

29.120 inches

Overall Width:

8.700 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

End Application:

Jp-5 fueling/defueling pump, spraytight motor; cvn77

Fuse Accommodation Quantity:

6

Size Designator:

1

Duty Cycle:

Continuous

Mounting Configuration:

Four 0.656dia holes for 0.625dia mounting bolts

Operating Voltage Characteristic:

Full

Horsepower Rating:

5.000 and 10.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

5.0 and 10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Watertight and dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

18.0

Switch Functional Positions:

Start and stop and reset and emergency run

Control Type:

Local or remote

Features Provided:

Accessory location external and circuit protection fuse

Product Name:

Controller a.C. Magnetic size 1

Phase:

Three

Special Features:

Contract no.N00024-98-c-2104modp00031; there are approved exceptions to mil-c-2212 concerning overload relay amperage-see drawing 6962ed3688; shockproof grade a class 1 of mil-s-901

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541b0