NSN 6110-01-537-2199

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-537-2199

Hazardous Locations/environmental Protection:
Submersible
Overall Length:
20.500 inches
Overall Height:
31.120 inches
Overall Width:
10.700 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Jp-5 transfer/stripping pump
Fuse Accommodation Quantity:
2
Size Designator:
2
Duty Cycle:
Continuous
Mounting Configuration:
Six holes 0.656dia for 0.625dia mounting bolts
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000 and 25.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Submersible
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:
Low start and high start and stop and reset and emergency run

NSN 6110-01-537-2199Motor Controller - Page 2 of 2



Control Type:	
Local or remote	
Features Provided:	
Accessory location external and circuit protection fuse	
Product Name:	
Controller a.C. Magnetic size 2/1	
Phase:	
Three	
Special Features:	
Enclosure submersible to 15 feet; exceptions to mil-c-2212 are overload relays-see drawing; shockproof grade a class 1 of mil-s-901;	
controller is nema size is 2/1	
Frequency In Hertz:	
60.0	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A541b0	