## NSN 6110-01-538-2789

Motor Controller - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-538-2789

Hazardous Locations/environmental Protection:
Submersible
Overall Length:
24.500 inches
Overall Height:
37.500 inches
Overall Width:
35.340 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
End Application:
Pump motor; cvn77
Fuse Accommodation Quantity:
2
Size Designator:
5
Duty Cycle:
Continuous
Mounting Configuration:
Six holes 0.656dia for 0.625dia mounting bolts
Operating Voltage Characteristic:
Full
Horsepower Rating:
200.000
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Submersible
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:
Start and stop and emergency stop and reset and emergency run

## NSN 6110-01-538-2789

Motor Controller - Page 2 of 2



Control Type:
Local or remote
Features Provided:
Accessory location external and circuit protection fuse
Product Name:
Controller a.C. Magnetic size 5
Phase:
Three
Special Features:
Submersible to 15 feet; shockproof grade a class 1 of mil-s-901; remote stop-start interlock 24vdc; thermistor included; 4 are required per
vessel
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541b0