

View Online at <https://aerobasegroup.com/nsn/6110-01-539-1549>

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

14.000 inches

**Overall Height:**

16.000 inches

**Overall Width:**

8.000 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**End Application:**

Transfer pump & evacuation motor

**Fuse Accommodation Quantity:**

4

**Size Designator:**

0

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Four holes 0.938dia for 0.438dia mounting bolts

**Operating Voltage Characteristic:**

Full

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

5.0 and 10.0

**Load Protection Type:**

Overload and undervoltage

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Dripproof

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Start and stop and reset

**Control Type:**

Local or remote

**Features Provided:**

Accessory location external and circuit protection fuse

**Product Name:**

Size 0 a.C. Magnetic controller assembly

**Phase:**

Three

**Special Features:**

Shockproof grade a class 1 of mil-s-901

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541b0