

| Motor Controller - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/6110-01-539-7332 |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 17.380 inches |
| Overall Height: |
| 27.120 inches |
| Overall Width: |
| 9.980 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| End Application: |
| Padeye operations motor |
| Fuse Accommodation Quantity: |
| 2 |
| Size Designator: |
| 2 |
| Duty Cycle: |
| |

Continuous

Mounting Configuration:

Four holes 0.656dia for 0.625dia mounting bolts

Operating Voltage Characteristic:

Full

Horsepower Rating:

25.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

5.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Watertight

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Up and down and reset and emergency run

NSN 6110-01-539-7332

Motor Controller - Page 2 of 2



Control Type:

Remote

Features Provided:

Accessory location external and circuit protection fuse

Product Name:

Controller a.C. Magnetic size 2

Phase:

Three

Special Features:

Shockproof grade a, class 1 of mil-s-901

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0