

6-4583

Motor Controller - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/6110-01-546
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
22.120 inches
Overall Height:
28.120 inches
Overall Width:
10.520 inches
Actuation Method:
Magnetic
End Application:
Supply ventalation fan s340 (3-42-2) two speed
Performance Type:
Automatic or manual
Fuse Accommodation Quantity:
4
Size Designator:
2/1
Duty Cycle:
Continuous
Mounting Configuration:
6 holes 0.531dia for 0.500 mounting bolts
Operating Voltage Characteristic:
Full

Horsepower Rating:

10.000 and 25.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

#### **Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:** 

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

18.0 and 45.0

**Switch Functional Positions:** 

Slow and fast and stop

# NSN 6110-01-546-4583

Motor Controller - Page 2 of 2



**Control Type:** 

Remote or local

## **Features Provided:**

Circuit protection fuse and accessory location external

## **Product Name:**

Controller a.C. Magnetic size 2/1

Phase:

Three

**Special Features:** 

Shiockproof grade a class 1 of mil-s-901

## **Frequency In Hertz:**

60.0

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A541b0