

View Online at <https://aerobasegroup.com/nsn/6110-01-595-6479>

Special Features:

Fabs v2 120v power conditioner with ups. Includes (1) furman pl-pro dmc power conditioner, (1) tripp lite smart online 1500va ups, and (1) support packaging case and connectors. output current: 15 amps. Line cord: captive 3/14 awg, 10 ft. Black cord with nema 15 plug, pull-out lights: two multi-led, dimmable lamps, bnc socket w/switch: rear rack lamp, 12vac 500ma maxx (lamp not included), operating voltage: 90 to 139 vac spike protection mode: line to neutral, zero ground leakage, spike clamping voltage: 188 vac peak @ 3, 000 amps, response time: 1 nanosecond, surge current: 6, 500 amps, noise attenuation: 10 db @ 10 khz, 40 db @ 100 khz, 50 db @ 500 khz , ups specifications: on-line input voltage: ac 100/110/120 v input voltage range: ac 65 - 138 v, frequency required: 50/60 hz, input connecto (s): 1 x power nema 5-15, output voltage: ac 100/110/120 v 2% (50/60 hz) , power output connectors details: 6 x power nema 5-15, power provided: 1.2 kw/ 1500 va d

Supplementary Features:

Ataline surge protection network/phone line - rj-45 output waveform: sinewave, surge suppression standard surge energy rating: 570 joules circuit protection circuit breaker battery type: expandable technology lead acid voltage provided: 48 v, run time: (up to) 4.5 min at full load recharge time 6 hou (s)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900