

View Online at <https://aerobasegroup.com/nsn/6110-01-595-9001>

Special Features:

Fabs v2 240v power conditioner with ups. Includes (1) furman pl-pro dmc e power conditioner, (1) tripp lite smart online suint1500rtxl2ua ups, and (1) support packaging case and connectors. Power conditioner specifications: output current: 16 amps, line cord: 3/1.0mm awg, 2.5m cord w/iec female to 10a schuko plug, pull-out lights: two multi-led, dimmable lamps, bnc socket w/switch: rear rack lamp, 12vac 500ma maxx (lamp not included), operating voltage: 180 to 274 vac, spike protection mode: line to neutral, zero ground leakage, spike clamping voltage: 375 vac peak @ 3,000 amps, response time: 1 nanosecond, surge current: 6,500 amps, noise attenuation: 10 db @ 10 khz, 40 db @ 100 khz, 50 db @ 500 khz

Supplementary Features:

Ups specifications: input voltage: ac 200/208/220/230/240 v, input voltage range: ac 130 - 275 v, frequency required: 50/60 hz input connecto (s) 1 x power iec 320 en 60320 c14, output voltage : ac 200/208/220/230/240 v 2% (50/60 hz) power output connectors details: 6 x power iec 320 en 60320 c13, power provided: 1.2 kw / 1500 va, dataline surge protection: phone line - rj-11, output waveform: sinewave, surge suppression standard surge energy rating: 660 joules, circuit protection: circuit breaker, battery technology: lead acid, voltage provided: 48 v run time (up to) 5 min at full load recharge time: 6 hour(s)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900