

View Online at <https://aerobasegroup.com/nsn/6115-00-017-8237>

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid shock tubular frame

Overall Length:

35.000 inches

Overall Height:

25.000 inches

Overall Width:

24.140 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz and 60.0 hertz and 60.0 hertz and 60.0 hertz

Accessory Component Quantity:

1

Document Type:

Military specification

Document Identification:

Mil-g-52732-6

Component Document Page Number:

2

Accessory Controlling Agency:

Army

Accessory Identifying Number:

Kit97403-1 part no.

Winterization Feature:

Not included

Ac Wattage Rating:

3.0 kilowatts and 3.0 kilowatts and 3.0 kilowatts and 3.0 kilowatts

Line To Line Voltage In Volts:

240.0 and 208.0 and 120.0 and 120.0

Line To Neutral Voltage In Volts:

120.0

Power Factor In Percent:

0.8 and 0.8 and 0.8 and 0.8

Excitor Type:

Self-excited

Prime Mover Starting Method:

Manually by rope

Automatic Starting Feature:

Not provided

Prime Mover Manufacturer Name:

Military standard engine

Prime Mover Identifying Number:

4a032-1 or -2 model no.

Housing Type:

Open

Accessory Component Name:

Electric start kit

Ambient Temperature In Deg Celsius:

-31.7 and 51.7

Temperature Rise Rating In Deg Celsius For Continuous Operation:

75.0

Radio Interference Suppression:

Included

Document Controlling Agency:

Army

Phase:

Single and three and single and three

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T322-a

Mil-std (military Standard):

Mil-g-52732 spec.