

View Online at <https://aerobasegroup.com/nsn/6115-00-017-8238>

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid shock tubular frame

**Overall Length:**

35.000 inches

**Overall Height:**

25.000 inches

**Overall Width:**

24.562 inches

**Current Type:**

Ac

**Frequency Rating:**

400.0 hertz

**End Application:**

Military standard engines and repair parts

**Winterization Feature:**

Not included

**Ac Wattage Rating:**

3.0 kilowatts

**Line To Line Voltage In Volts:**

240.0 and 120.0 and 208.0

**Line To Neutral Voltage In Volts:**

120.0

**Power Factor In Percent:**

80.0

**Excitor Type:**

Self-excited

**Prime Mover Starting Method:**

Manually by rope

**Automatic Starting Feature:**

Not provided

**Prime Mover Manufacturer Name:**

6 hp military standard engine

**Prime Mover Identifying Number:**

4a032-1, -2 model no.

**Housing Type:**

Open

**Ambient Temperature In Deg Celsius:**

-31.7 and 51.7

**Temperature Rise Rating In Deg Celsius For Continuous Operation:**

75.0

**Radio Interference Suppression:**

Included

**Phase:**

Single or three

**Special Features:**

Can be equipped with electric starting kit for starting from an external 24 v source

**Specification Or Standard:**

I type and 2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T322-a