

View Online at <https://aerobasegroup.com/nsn/6115-00-077-8598>

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid shock tubular frame

**Overall Length:**

45.000 inches

**Overall Height:**

34.000 inches

**Overall Width:**

29.000 inches

**Current Type:**

Ac

**Frequency Rating:**

400.0 hertz and 400.0 hertz and 400.0 hertz and 400.0 hertz

**Winterization Feature:**

Included

**Ac Wattage Rating:**

5.0 kilowatts and 5.0 kilowatts and 5.0 kilowatts and 5.0 kilowatts

**Line To Line Voltage In Volts:**

240.0 and 208.0 and 120.0 and 120.0

**Line To Neutral Voltage In Volts:**

120.0

**Power Factor In Percent:**

0.8 and 0.8 and 0.8 and 0.8

**Excitor Type:**

Separately excited

**Excitor:**

Included

**Prime Mover Starting Method:**

Electric motor

**Cranking Voltage In Volts:**

24.0

**Automatic Starting Feature:**

Not provided

**Prime Mover Manufacturer Name:**

N/a

**Housing Type:**

Open

**Ambient Temperature In Deg Celsius:**

-54.0 and 52.0

**Temperature Rise Rating In Deg Celsius For Continuous Operation:**

65.0

**Radio Interference Suppression:**

Included

**Phase:**

Three and three and three and single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T322-a