

View Online at <https://aerobasegroup.com/nsn/6115-00-133-9102>

Prime Mover Cooling Medium:

Liquid

Mounting Type:

Skid

Overall Length:

106.000 inches

Overall Height:

65.000 inches

Overall Width:

40.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Cooling Method:

Radiator

Inclosure Type:

Fully enclosed

Winterization Feature:

Not included

Ac Wattage Rating:

100.0 kilowatts and 100.0 kilowatts and 83.3 kilowatts and 83.3 kilowatts

Line To Line Voltage In Volts:

416.0 and 208.0 and 416.0 and 208.0

Line To Neutral Voltage In Volts:

240.0 and 120.0 and 240.0 and 120.0

Power Factor In Percent:

0.8 and 0.8 and 0.8 and 0.8

Excitor Type:

Separately excited

Excitor:

Included

Prime Mover Starting Method:

Electric motor

Cranking Voltage In Volts:

24.0

Automatic Starting Feature:

Not provided

Housing Type:

Inclosed

Ambient Temperature In Deg Celsius:

51.7

Temperature Rise Rating In Deg Celsius For Continuous Operation:

50.0

Radio Interference Suppression:

Included

Phase:

Three and three and three and three

Special Features:

Precise electronic load sensing governor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T322-a