

View Online at <https://aerobasegroup.com/nsn/6115-00-548-1377>

Prime Mover Cooling Medium:

Liquid

Mounting Type:

Skid

Overall Length:

48.000 inches

Overall Height:

37.000 inches

Overall Width:

28.000 inches

Current Type:

Ac and dc

Direct Current Rating In Amps:

89.0

Dc Voltage Rating:

28.0 volts

Frequency Rating:

400.0 hertz and 400.0 hertz and 400.0 hertz

Cooling Method:

Radiator

Maximum Weight Capacity:

1250.000 pounds

End Application:

6115-00-548-1377 type no. An/gss-1 series

Winterization Feature:

Included

Ac Wattage Rating:

10.0 kilovolt-ampere and 10.0 kilovolt-ampere and 12.5 kilovolt-ampere

Dc Wattage Rating:

2.5 kilowatts

Line To Line Voltage In Volts:

120.0 and 208.0 and 120.0 and 208.0

Line To Neutral Voltage In Volts:

120.0

Power Factor In Percent:

0.8 and 0.8 and 0.8

Excitor Type:

Self-excited

Excitor:

Included

Prime Mover Starting Method:

Battery and manually by crank

Cranking Voltage In Volts:

12.0

Automatic Starting Feature:

Not provided

Prime Mover Manufacturer Name:

N/a

Housing Type:

Open

Ambient Temperature In Deg Celsius:

52.0

Temperature Rise Rating In Deg Celsius For Continuous Operation:

40.0 and 65.0

Radio Interference Suppression:

Included

Phase:

Single and three and three

Special Features:

Tropicalized

Specification Or Standard:

Pu-107/u type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T322-a