## NSN 6115-00-635-8612

Direct Current Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6115-00-635-8612

Overall Height:
10.9062 inches
Overall Length:
15.9375 inches
Overall Width:
7.250 inches
Maximum Operating Altitude Rating:
50000.0 feet
Shaft Rotation Direction:
Counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Winding Type:
Shunt wound
Mounting Facility Type And Quantity:
6 unthreaded hole
Excitor Type:
Self-excited
Inclosure Specificationification:
Inclosure Specificationification:  Commercial
Commercial
Commercial  Power Rating:
Commercial  Power Rating:  9.000 kilowatts output
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:
Commercial  Power Rating: 9.000 kilowatts output  Length Of Shaft From Housing: 1.000 inches single end
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches
Commercial  Power Rating: 9.000 kilowatts output  Length Of Shaft From Housing: 1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length: 6.750 inches  Tempurature Rating:
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius  Rotor Speed Rating In Rpm:
Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius  Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius  Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load  Center To Center Distance Between Mounting Facilities Parallel To Width:
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius  Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load  Center To Center Distance Between Mounting Facilities Parallel To Width:  2.500 inches
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load  Center To Center Distance Between Mounting Facilities Parallel To Width:  2.500 inches  Current Rating In Amps:
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load  Center To Center Distance Between Mounting Facilities Parallel To Width:  2.500 inches  Current Rating In Amps:  300.000 single output
Commercial  Power Rating:  9.000 kilowatts output  Length Of Shaft From Housing:  1.000 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  6.750 inches  Tempurature Rating:  -55.0 operating degrees celsius and 40.0 operating degrees celsius and 125.0 ambient degrees celsius Rotor Speed Rating In Rpm:  3000.0 low full load and 8000.0 high full load  Center To Center Distance Between Mounting Facilities Parallel To Width:  2.500 inches  Current Rating In Amps:  300.000 single output  Connection Type And Voltage Rating In Volts:

N/a

Shelf Life:

## NSN 6115-00-635-8612

Direct Current Generator - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A271a0