

View Online at <https://aerobasegroup.com/nsn/6115-00-643-4674>

Body Material:

Steel

Current Type:

Ac and dc

Direct Current Rating In Amps:

357.1 and 428.6

Dc Voltage Rating:

28.0 volts

Frequency Rating:

400.0 hertz and 400.0 hertz and 400.0 hertz

End Application:

Type no. An/mpq-4a

Wheel Quantity:

2

Body Type:

Box

Document Type:

Technical manual

Document Identification:

Tm-11-1367 (1960+eckx

Item Name Assigned By Government Agency:

Generator set, gasoline engine, trailer mtd

Identifying Number:

Permanent magnet type

Winterization Feature:

Not included

Manufacturer Name:

Okeef-merritt co

Load Capacity:

1.50 tons

Ac Wattage Rating:

10.0 kilowatts and 10.0 kilowatts and 12.5 kilowatts

Dc Wattage Rating:

2.5 kilowatts

Line To Line Voltage In Volts:

120.0 and 280.0 and 208.0

Line To Neutral Voltage In Volts:

120.0 and 280.0 and 208.0

Power Factor In Percent:

80.0 and 80.0 and 80.0

Excitor Type:

Self-excited

Excitor:

Not included

Prime Mover Manufacturer Name:

Willys overland co

Prime Mover Identifying Number:

807532 model no.

Hitch/coupler Style:

Spring cushioned lunette coupler

Ambient Temperature In Deg Celsius:

50.0

Tempurature Rise Rating In Deg Celsius For Continuous Operation:

40.0

Radio Interference Suppression:

Included

Document Controlling Agency:

Sig

Phase:

Single and three and three

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T322-a