

View Online at <https://aerobasegroup.com/nsn/6115-00-697-2402>

Body Material:

Wood and steel

Current Type:

Ac and dc

Direct Current Rating In Amps:

357.1

Dc Voltage Rating:

28.0 volts

Frequency Rating:

400.0 hertz

Accessory Component Quantity:

2 and 6 and 2 and 2 and 1 and 1 and 2 and 1

Wheel Quantity:

2

Body Type:

Box type body w/lattice type sidetxtensions

Item Name Assigned By Government Agency:

Generator set, gasoline engine, trailer mounted

Accessory Controlling Agency:

Army engineer research and development laboratories; dgsc; dcsc; u. S. Army mobility equipment center; gsa; dgsc; dgsc; tacom

Accessory Identifying Number:

13211e7541 part no. And mil-c-1283a /7240-555-3088/ and mil-e-52031 /4210-555-8837/ and mil-p-11122 /6115-548-1377/ and federal specification ggg-h-86 /5120-251-4489/ and mil-r-11461 /6975-878-3791/ and mil-s-1285 /7240-177-6154/ and -105a2 /2330-141-8050/ model no.

Winterization Feature:

Included

Load Capacity:

1.50 tons

Ac Wattage Rating:

10.0 kilowatts

Dc Wattage Rating:

2.5 kilowatts

Line To Line Voltage In Volts:

120.0 and 208.0

Line To Neutral Voltage In Volts:

120.0 and 208.0

Power Factor In Percent:

0.8

Excitor Type:

Self-excited

Hitch/coupler Style:

Spring cushioned lunette coupler

Accessory Component Name:

Adapter assembly, fuel drum; can, gasoline, military; extinguisher, fire, monobromotrifluoromethane; generator set, gasoline engine;

hammer, hand; red, ground; spout, can, flexible; trailer, cargo

Ambient Temperature In Deg Celsius:

-53.9 and 51.7

Temperature Rise Rating In Deg Celsius For Continuous Operation:

75.0

Radio Interference Suppression:

Included

Phase:

Single/three

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T322-a