

View Online at <https://aerobasegroup.com/nsn/6115-00-697-2402>

**Body Material:**

Wood and steel

**Current Type:**

Ac and dc

**Direct Current Rating In Amps:**

357.1

**Dc Voltage Rating:**

28.0 volts

**Frequency Rating:**

400.0 hertz

**Accessory Component Quantity:**

2 and 6 and 2 and 2 and 1 and 1 and 2 and 1

**Wheel Quantity:**

2

**Body Type:**

Box type body w/lattice type sidetxtensions

**Item Name Assigned By Government Agency:**

Generator set, gasoline engine, trailer mounted

**Accessory Controlling Agency:**

Army engineer research and development laboratories; dgsc; dcsc; u. S. Army mobility equipment center; gsa; dgsc; dgsc; tacom

**Accessory Identifying Number:**

13211e7541 part no. And mil-c-1283a /7240-555-3088/ and mil-e-52031 /4210-555-8837/ and mil-p-11122 /6115-548-1377/ and federal specification ggg-h-86 /5120-251-4489/ and mil-r-11461 /6975-878-3791/ and mil-s-1285 /7240-177-6154/ and -105a2 /2330-141-8050/ model no.

**Winterization Feature:**

Included

**Load Capacity:**

1.50 tons

**Ac Wattage Rating:**

10.0 kilowatts

**Dc Wattage Rating:**

2.5 kilowatts

**Line To Line Voltage In Volts:**

120.0 and 208.0

**Line To Neutral Voltage In Volts:**

120.0 and 208.0

**Power Factor In Percent:**

0.8

**Excitor Type:**

Self-excited

**Hitch/coupler Style:**

Spring cushioned lunette coupler

**Accessory Component Name:**

Adapter assembly, fuel drum; can, gasoline, military; extinguisher, fire, monobromotrifluoromethane; generator set, gasoline engine; hammer, hand; rod, ground; spout, can, flexible; trailer, cargo

**Ambient Temperature In Deg Celsius:**

-53.9 and 51.7

**Temperature Rise Rating In Deg Celsius For Continuous Operation:**

75.0

**Radio Interference Suppression:**

Included

**Phase:**

Single/three

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T322-a