

View Online at <https://aerobasegroup.com/nsn/6115-00-719-6122>

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid

Overall Length:

60.000 inches

Overall Height:

39.000 inches

Overall Width:

40.000 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz

Document Type:

Military specification

Document Identification:

Mil-g-38025c

Component Document Page Number:

43

Inclosure Type:

Fully enclosed

Identifying Number:

Part no. 13380

Winterization Feature:

Included

Manufacturer Name:

Lima electric motor co

Ac Wattage Rating:

10.0 kilowatts and 10.0 kilowatts and 10.0 kilowatts and 10.0 kilowatts

Line To Line Voltage In Volts:

120.0 and 120.0 and 208.0 and 240.0

Power Factor In Percent:

0.8 and 0.8 and 0.8 and 0.8

Excitor Type:

Self-excited

Prime Mover Starting Method:

Electric motor

Cranking Voltage In Volts:

24.0

Automatic Starting Feature:

Provided

Prime Mover Manufacturer Name:

Prestolite div of eltra corp

Prime Mover Identifying Number:

Part no. M3p4012t

Housing Type:

Inclosed

Ambient Temperature In Deg Celsius:

50.0

Tempurature Rise Rating In Deg Celsius For Continuous Operation:

130.0

Radio Interference Suppression:

Included

Document Controlling Agency:

Air force

Phase:

Three and single and three and single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T322-a

Mil-std (military Standard):

Mil-g-38025 spec.