

View Online at <https://aerobasegroup.com/nsn/6115-00-738-6340>

Body Material:

Steel

Current Type:

Ac

Frequency Rating:

60.0 hertz

Accessory Component Quantity:

2 and 1 and 6 and 1 and 1 and 2 and 2 and 1 and 2

Wheel Quantity:

2

Body Type:

Flat bed

Accessory Controlling Agency:

Dcsc; u.S. Army mobility equipment command; dgsc; atac; u.S. Army mobility equipment command; dcsc; u.S army mobility equipment command; gsa; dgsc

Accessory Identifying Number:

13211e7541 part no. And 13214e1202 /2510-922-6473/ part no. And military specification mil-c-1283 /7240-222-3088/ and -116a /2330-898-6780/ model no. And 13212e3601 /6110-913-9275/ part no. And military specification mil-e-52031 /4210-555-8837/ and military specification mil-g-52279 /6115-017-8240/ and federal specification ggg h-86 /5120-251-4489/ and military specification mil-r-11461 /5975-878-3791/

Winterization Feature:

Not included

Load Capacity:

0.750 tons

Ac Wattage Rating:

5.0 kilowatts

Line To Line Voltage In Volts:

120.0 and 208.0 and 240.0

Power Factor In Percent:

0.8

Excitor Type:

Self-excited

Hitch/coupler Style:

Plain, offset, lunette type coupler

Accessory Component Name:

Gadapter assembly, fuel tank; body, trailer; can, gasoline, military; chassis, trailer; distribution box; extinguisher, fire, monobromotrifluoromethane; generator set, gasoline engine; hammer, hand; rod, ground

Ambient Temperature In Deg Celsius:

-53.9 and 51.7

Tempurature Rise Rating In Deg Celsius For Continuous Operation:

75.0

Radio Interference Suppression:

Included

Phase:

Single and three

Unit Of Measure:

--

Demilitarization:

No

Fig:

T322-a

Mil-std (military Standard):

Mil-c-1283 spec.