

View Online at <https://aerobasegroup.com/nsn/6115-00-738-6340>

**Body Material:**

Steel

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Accessory Component Quantity:**

2 and 1 and 6 and 1 and 1 and 2 and 2 and 1 and 2

**Wheel Quantity:**

2

**Body Type:**

Flat bed

**Accessory Controlling Agency:**

Dcsc; u.S. Army mobility equipment command; dgsc; atac; u.S. Army mobility equipment command; dcsc; u.S army mobility equipment command; gsa; dgsc

**Accessory Identifying Number:**

13211e7541 part no. And 13214e1202 /2510-922-6473/ part no. And military specification mil-c-1283 /7240-222-3088/ and -116a /2330-898-6780/ model no. And 13212e3601 /6110-913-9275/ part no. And military specification mil-e-52031 /4210-555-8837/ and military specification mil-g-52279 /6115-017-8240/ and federal specification ggg h-86 /5120-251-4489/ and military specification mil-r-11461 /5975-878-3791/

**Winterization Feature:**

Not included

**Load Capacity:**

0.750 tons

**Ac Wattage Rating:**

5.0 kilowatts

**Line To Line Voltage In Volts:**

120.0 and 208.0 and 240.0

**Power Factor In Percent:**

0.8

**Excitor Type:**

Self-excited

**Hitch/coupler Style:**

Plain, offset, lunette type coupler

**Accessory Component Name:**

Gadapter assembly, fuel tank; body, trailer; can, gasoline, military; chassis, trailer; distribution box; extinguisher, fire, monobromotrifluoromethane; generator set, gasoline engine; hammer, hand; rod, ground

**Ambient Temperature In Deg Celsius:**

-53.9 and 51.7

**Tempurature Rise Rating In Deg Celsius For Continuous Operation:**

75.0

**Radio Interference Suppression:**

Included

**Phase:**

Single and three

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T322-a

**Mil-std (military Standard):**

Mil-c-1283 spec.