NSN 6115-00-889-1446

Gasoline Engine Generator Set - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6115-00-889-1446

| Prime Mover Cooling Medium: |
|--|
| Air |
| Mounting Type: |
| Skid shock tubular frame |
| Overall Length: |
| 27.375 inches |
| Overall Height: |
| 18.500 inches |
| Overall Width: |
| 20.375 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Maximum Weight Capacity: |
| 125.000 pounds |
| Winterization Feature: |
| Not included |
| Ac Wattage Rating: |
| 1.5 kilowatts |
| Line To Line Voltage In Volts: |
| 120.0 and 240.0 |
| Line To Neutral Voltage In Volts: |
| 120.0 |
| Power Factor In Percent: |
| 100.0 |
| Excitor Type: |
| Self-excited |
| Prime Mover Starting Method: |
| Manually by rope |
| Automatic Starting Feature: |
| Not provided |
| Prime Mover Manufacturer Name: |
| Military standard by military departments |
| Prime Mover Identifying Number: |
| Ms39298 part no. |
| Housing Type: |
| Open |
| Ambient Tempurature In Deg Celsius: |
| -31.7 and 51.7 |
| Tempurature Rise Rating In Deg Celsius For Continuous Operation: |

75.0

NSN 6115-00-889-1446

Gasoline Engine Generator Set - Page 2 of 2



| Radio Interference Suppression: |
|---------------------------------|
| Included |
| Phase: |
| Single |
| Specification Or Standard: |
| 1 type and 2 class |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T322-a |
| Mil-std (military Standard): |

Mil-g-52282 spec.