NSN 6115-00-920-2390

Prime Mover Cooling Medium:

Liquid

Diesel Engine Generator Set - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6115-00-920-2390

| Mounting Type: |
|-------------------------------------|
| Skid |
| Overall Length: |
| 96.000 inches |
| Overall Height: |
| 51.500 inches |
| Overall Width: |
| 40.5625 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Cooling Method: |
| Radiator |
| Inclosure Type: |
| Fully enclosed |
| Winterization Feature: |
| Not included |
| Ac Wattage Rating: |
| 100.0 kilowatts and 100.0 kilowatts |
| Line To Line Voltage In Volts: |
| 416.0 and 208.0 |
| Line To Neutral Voltage In Volts: |
| 240.0 and 120.0 |
| Power Factor In Percent: |
| 0.8 and 0.8 |
| Excitor Type: |
| Self-excited |
| Prime Mover Starting Method: |
| Electric motor |
| Cranking Voltage In Volts: |
| 24.0 |
| Automatic Starting Feature: |
| Not provided |
| Prime Mover Manufacturer Name: |
| Caterpiller tractor co |
| Prime Mover Identifying Number: |
| Model no. D333 |
| Housing Type: |
| Inclosed |
| |
| |

NSN 6115-00-920-2390

Fiig: T322-a

Diesel Engine Generator Set - Page 2 of 2



| Ambient Tempurature in Deg Ceisius: | |
|--|--|
| 40.0 | |
| Tempurature Rise Rating In Deg Celsius For Continuous Operation: | |
| 40.0 | |
| Radio Interference Suppression: | |
| Not included | |
| Phase: | |
| Three and three | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |