

View Online at <https://aerobasegroup.com/nsn/6115-00-975-8381>

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid shock tubular frame

Overall Length:

31.875 inches

Overall Height:

27.875 inches

Overall Width:

22.875 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz and 60.0 hertz and 60.0 hertz and 60.0 hertz

Winterization Feature:

Included

Ac Wattage Rating:

3.0 kilowatts and 3.0 kilowatts and 3.0 kilowatts and 3.0 kilowatts

Line To Line Voltage In Volts:

240.0 and 208.0 and 120.0 and 120.0

Line To Neutral Voltage In Volts:

120.0 and 120.0

Power Factor In Percent:

0.8 and 0.8 and 0.8 and 0.8

Excitor Type:

Separately excited

Excitor:

Included

Prime Mover Starting Method:

Manually by rope

Automatic Starting Feature:

Not provided

Housing Type:

Open

Ambient Temperature In Deg Celsius:

-54.0 and 52.0

Temperature Rise Rating In Deg Celsius For Continuous Operation:

40.0

Radio Interference Suppression:

Included

Phase:

Single and three and three and single

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T322-a