

View Online at <https://aerobasegroup.com/nsn/6115-01-256-1058>

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid shock tubular frame

**Overall Length:**

24.100 inches

**Overall Height:**

18.800 inches

**Overall Width:**

14.800 inches

**Current Type:**

Ac and dc

**Direct Current Rating In Amps:**

8.3

**Dc Voltage Rating:**

12.0 volts

**Frequency Rating:**

60.0 hertz

**Accessory Component Quantity:**

9

**Accessory Controlling Agency:**

Yanmar diesel engine co., ltd

**Winterization Feature:**

Not included

**Unpackaged Unit Weight:**

130.000 pounds

**Ac Wattage Rating:**

2.0 kilowatts

**Dc Wattage Rating:**

100.0 watts

**Line To Line Voltage In Volts:**

120.0

**Line To Neutral Voltage In Volts:**

120.0

**Power Factor In Percent:**

100.0

**Excitor Type:**

Self-excited

**Excitor:**

Included

**Prime Mover Starting Method:**

Electric motor or manually by rope

**Automatic Starting Feature:**

Not provided

**Prime Mover Manufacturer Name:**

Yanmar diesel engine co., ltd

**Prime Mover Identifying Number:**

L40e model no.

**Housing Type:**

Open

**Accessory Component Name:**

Pilot lamp; ac voltmeter; ac receptacle; dc receptacle; braker; fuse; key switch; oil alert; stop solenoid

**Ambient Temperature In Deg Celsius:**

20.0

**Radio Interference Suppression:**

Not included

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T322-a